

RATE OF CLIMB BELL-206

Calcolare il rate of climb con anti-ice OFF e anti-ICE ON nelle situazioni proposte qui di seguito.

Es-1	OTA: -9 [C°]
	PA: 20000 [hPa]
	WEIGHT: 2200 [ibs]

Es-2	OTA: 23 [C°]
	PA: 6000 [hPa]
	WEIGHT: 3000 [ibs]

Es-3	OTA: 6 [C°]
	PA: 12000 [hPa]
	WEIGHT: 2600 [ibs]

Es-4	OTA: -2 [C°]
	PA: 14000 [hPa]
	WEIGHT: 2000 [ibs]

Es-5	OTA: 31 [C°]
	PA: 4000 [hPa]
	WEIGHT: 2400 [ibs]

Es-6	OTA: -15 [C°]
	PA: 16000 [hPa]
	WEIGHT: 3200 [ibs]

Es-7	OTA: 6 [C°]
	PA: 10000 [hPa]
	WEIGHT: 3200 [ibs]

Es-8	OTA: 16 [C°]
	PA: 8000 [hPa]
	WEIGHT: 2800 [ibs]

Es-9	OTA: 4 [C°]
	PA: 18000 [hPa]
	WEIGHT: 2200 [ibs]

Es-10	OTA: 39 [C°]
	PA: 2000 [hPa]
	WEIGHT: 2600 [ibs]

RATE OF CLIMB BELL-206

Es-1	ROC Anti-Ice OFF:	461 [ft/min]
	Δ ROC Anti-ICE ON:	296 [ft/min]
	ROC Anti-Ice ON:	165 [ft/min]
Es-2	ROC Anti-Ice OFF:	847 [ft/min]
	Δ ROC Anti-ICE ON:	331 [ft/min]
	ROC Anti-Ice ON:	516 [ft/min]
Es-3	ROC Anti-Ice OFF:	955 [ft/min]
	Δ ROC Anti-ICE ON:	341 [ft/min]
	ROC Anti-Ice ON:	614 [ft/min]
Es-4	ROC Anti-Ice OFF:	1598 [ft/min]
	Δ ROC Anti-ICE ON:	399 [ft/min]
	ROC Anti-Ice ON:	1200 [ft/min]
Es-5	ROC Anti-Ice OFF:	1674 [ft/min]
	Δ ROC Anti-ICE ON:	405 [ft/min]
	ROC Anti-Ice ON:	1269 [ft/min]
Es-6	ROC Anti-Ice OFF:	42 [ft/min]
	Δ ROC Anti-ICE ON:	258 [ft/min]
	ROC Anti-Ice ON:	-217 [ft/min]
Es-7	ROC Anti-Ice OFF:	516 [ft/min]
	Δ ROC Anti-ICE ON:	301 [ft/min]
	ROC Anti-Ice ON:	215 [ft/min]
Es-8	ROC Anti-Ice OFF:	1042 [ft/min]
	Δ ROC Anti-ICE ON:	348 [ft/min]
	ROC Anti-Ice ON:	693 [ft/min]
Es-9	ROC Anti-Ice OFF:	484 [ft/min]
	Δ ROC Anti-ICE ON:	298 [ft/min]
	ROC Anti-Ice ON:	186 [ft/min]
Es-10	ROC Anti-Ice OFF:	1381 [ft/min]
	Δ ROC Anti-ICE ON:	379 [ft/min]
	ROC Anti-Ice ON:	1002 [ft/min]